



Cherry Wax Matte

PRODUCT DESCRIPTION: SS Cherry Wax Matte is designed as a sacrificial protective finish for many different surfaces where a durable and less shiny appearance is desired. SS Cherry Wax Matte has long term wear properties. SS Cherry Wax Matte can be maintained through regular maintenance procedures of dry and damp mopping with limited or frequent ultra high speed burnishing including the use of propane burnishing equipment. NOTE: Burnishing may increase the shine level. Educational institutions, health care facilities, large mall areas and chain retail stores are but a few of the applications where SS Cherry Wax Matte will yield durable results. The softer appearing finish shows exhibits fewer scuff marks and scratches than higher shine levels.

BENEFITS/FEATURES

- Non-shiny appearance.
- Rapid protective build.
- Balanced scuff and black mark resistance.
- Balanced detergent resistance and removability.
- Withstands repeated damp mop and machine scrub cycles.
- Exceptional application and lay-down characteristics.
- Non-flammable, non-combustible, non-corrosive. Not hazardous!

RECOMMENDED APPLICATIONS: SS Cherry Wax Matte is recommended for interior sealed applications where a less shiny and softer appearance is desired.

TECHNICAL INFORMATION

Solids.....	21%	Drying Time*.....	1-2 hours
Re-Coat Time	2-3 hours	Foot Traffic	12-24 hours
Wheel Traffic.....	24-48 hours	Application Temp	40°F - 85°F
Wet Appearance.....	Milky white	Dry Appearance.....	Crystal clear
VOC Content	None	Blush Resistance.	Excellent
Solvent Resistance.....	Good	Concrete Adhesion	Superior (over sealed surfaces)

*Please note that low air and/or concrete temperatures and/or relative humidity may extend drying times. Follow recommended coverage rates for best results.



Distributed by Cimarron Wholesale | 125 NE 40th Street
Oklahoma City, OK 73105 | Phone 866-906-2006 / Fax 405-526-2008

SPECIFICATIONS/COMPLIANCES: SS Cherry Wax Matte is VOC and OTC compliant in all areas of the United States and many foreign nations.

APPROXIMATE COVERAGE RATES:

<u>Application surface</u>	<u>First coat</u>	<u>Optional second coat</u>
Interior sealed surfaces	500-1000 ft ²	500-1000 ft ²

*Coverage rates vary depending upon surface porosity and texture, and application method. Follow directions for best results.

SHELF LIFE: SS Cherry Wax Matte has a shelf life of one-two years in its original, sealed, unopened container.

PACKAGING: SS Cherry Wax Matte is packaged and stocked in 1 gallon jugs and 5 gallon pails. 55 gallon drums are available on special order.

DIRECTIONS: Do not dilute. Pour on to sealed surface and mop using a synthetic mop or a rayon mop applicator. The floor may be maintained between coats of SS Cherry Wax Matte with a mild soap and water. Reapply SS Cherry Wax Matte on a regular basis to insure the protection of the floor sealer or coating. Note: SS Cherry Wax Matte is not a sealer, but is intended to protect and extend the life of the sealer.

CLEAN UP: Use warm soap and water. Dispose of containers in accordance with local and federal regulations.

PRODUCT REMOVAL: Product may be re-coated up to 100 times. When product removal is necessary, use a light ammonia and water solution to strip the waxed area back to the sealed surface.

PRECAUTIONS AND LIMITATIONS

- SS Cherry Wax Matte will freeze. It is recommended to store in an area between 50°F and 85°F recommended.
- Do not puddle or apply in thick coats. SS Cherry Wax Matte should be applied in several very thin coats.
- SS Cherry Wax Matte is harmful if swallowed. Abide by recommended safety guidelines.
- Coverage rates depend upon many conditions including application method, surface porosity, applicator, etc.
- SS Cherry Wax Matte was designed for interior use only. It is not recommended for exterior use.
- SS Cherry Wax Matte should only be diluted for spray buffing only. Do not dilute for normal use unless necessary.
- SS Cherry Wax Matte should only be used as a sacrificial coating and not used as a sealing *compound*.

SPECIAL NOTES: Please consult Material Safety Data Sheet (MSDS) and read Warranty information prior to use. This information can be requested by contacting customer service at 866-906-2006.