



Cherry Wax PLUS

PRODUCT DESCRIPTION: SS Specialties Cherry Wax Plus is a high performance cherry scented water based acrylic floor wax. It is perfect for small areas as well as large commercial areas as it can be applied by mop or high speed burnishing. SS Cherry Wax Plus yields rapid gloss build along with superior long-term wear characteristics. It's superior resistance to wet and dry traffic wear can yield a smooth polished look for months without maintenance. SS Cherry Wax Plus should be used on any sealed surface where a rapidly high gloss build and superior maintenance properties are desired.

BENEFITS/FEATURES

- Non-flammable, non-combustible, non-corrosive. Not hazardous!
- Great smelling cherry scent is very pleasing to the nose.
- This formula contains only environmentally safe materials.
- High solids provides superior sheen and resistance to abrasion and scuffing.

RECOMMENDED APPLICATIONS: SS Cherry Wax Plus is recommended for interior sealed applications where a high sheen polish is desired.

TECHNICAL INFORMATION

Solids.....28%	Drying Time* 1-2 hours
Re-Coat Time2-3 hours	Foot Traffic 12-24 hours
Wheel Traffic.....24-48 hours	Application 40°F - 85°F
Wet Appearance.....Milky white	Dry Appearance Crystal clear
VOC ContentNone	Blush Resistance. Excellent
Solvent Resistance.....Good	Concrete Adhesion Superior (over sealed surfaces)

*Please note that low air and/or concrete temperatures and/or relative humidity may extend drying times. Follow recommended coverage rates for best results.

SPECIFICATIONS/COMPLIANCES: SS Cherry Wax Plus is VOC and OTC compliant in all areas of the United States and many foreign nations.

APPROXIMATE COVERAGE RATES:

<u>Application surface</u>	<u>First coat</u>	<u>Optional second coat</u>
Interior sealed surfaces	500-1000 ft ²	500-1000 ft ²

*Coverage rates vary depending upon surface porosity and texture, and application method. Follow directions for best results.



Distributed by Cimarron Wholesale | 125 NE 40th Street
Oklahoma City, OK 73105 | Phone 866-906-2006 / Fax 405-526-2008

SHELF LIFE: SS Cherry Wax Plus has a shelf life of one-two years in its original, sealed, unopened container.

PACKAGING: SS Cherry Wax Plus is packaged and stocked in 1 gallon jugs and 5 gallon pails. 55 gallon drums are available on special order.

INSTRUCTIONS FOR USE: Preparation: Be sure the area of the concrete to be removed is free of trash and debris. Protect all other areas. Mask off all adjacent surfaces with painter's tape or plastic duct tape. If spray buffing, use a plastic or coated cardboard as a spray shield.

1. Do not apply by pouring directly onto surface. Use a plastic roller pan. Apply by synthetic fiber wax applicator, lambs wool applicator, or clean sponge mop.
2. Apply at a rate of 500-1000 square feet per gallon in very thin coats only. Apply in one direction to a consistent, even, and uniform finish. If puddling or pinholes appear, work them out into a thin coat.
3. Allow to dry 1-2 hours. Repeat process as many times as necessary to achieve required gloss build. If spray buffing, dilute wax 1:2 with water. Apply using a trig mist sprayer over a small area at a time. Buff that area until the liquid has disappeared and a superior shine is left. Continue this same process throughout the whole floor for high shine waxed floor. Periodic maintenance coats may be necessary as traffic will eventually dull the surface. Simply mop the area clean using a light detergent solution. Allow to dry and then apply a coat of SS Cherry Wax Plus to rejuvenate the smooth glossy finish.

CLEAN UP: Use warm soap and water. Dispose of containers in accordance with local and federal regulations.

PRODUCT REMOVAL: Product may be re-coated up to 100 times. When product removal is necessary, use a light ammonia and water solution to strip the waxed area back to the sealed surface.

PRECAUTIONS AND LIMITATIONS:

- SS Cherry Wax Plus will freeze. It is recommended to store in an area between 50°F and 85°F recommended.
- Do not puddle or apply in thick coats. SS Cherry Wax Plus should be applied in several very thin coats.
- SS Cherry Wax Plus is harmful if swallowed. Abide by recommended safety guidelines.
- Coverage rates depend upon many conditions including application method, surface porosity, applicator, etc.
- SS Cherry Wax Plus was designed for interior use only. It is not recommended for exterior use.
- SS Cherry Wax Plus should only be diluted for spray buffing only. Do not dilute for normal use unless necessary.
- SS Cherry Wax Plus should only be used as a sacrificial coating and not used as a sealing compound.

SPECIAL NOTES: Please consult Material Safety Data Sheet (MSDS) and read Warranty information prior to use. This information can be requested by contacting customer service at 866-906-2006.