

SECTION 1: PRODUCT INFORMATION CODE: 7065

**MANUFACTURER'S NAME / ADDRESS**

**CROSSFIELD PRODUCTS CORP.**  
 3000 E. HARCOURT ST.  
 RANCHO DOMINGUEZ, CA 90221  
 (310) 886-9100 (8:00a.m. to 5:00p.m. pacific time)  
 140 VALLEY RD.  
 ROSELLE PARK, NJ 07204  
 (908) 245-2800 (8:00 a.m. to 5:00 p.m. eastern time)  
 (800) 424-9300 (CHEMTREC)

**TRADE NAME:** MIRACOTE REPAIR MORTAR II DRY MIX  
**CHEMICAL FAMILY:** MODIFIED CEMENT MORTAR  
**INTENDED USE:** DECK COVERING POLYMER ADMIX  
**WHMIS CLASSIFICATION:** D2B

INITIAL ISSUE DATE: FEBRUARY 14, 2000 REVISED: APRIL 20, 2004 PREPARED BY: J.W. ESSIG

**SECTION 2: HAZARDOUS INGREDIENTS**

<b>INGREDIENTS</b>	<b>Wt. %</b>	<b>CAS Number</b>
SILICON DIOXIDE	60-100	014808-60-7
FUSED CALCIUM ALUMINATE	10-30	065997-16-2
ZINC OXIDE	0.1-1.0	001314-13-2

**EXPOSURE LIMITS (ppm)**

<b>INGREDIENTS (CAS)</b>	<b>OSHA</b>		<b>ACGIH</b>		<b>OTHER</b>
	<b>TWA</b>	<b>STEL</b>	<b>TWA</b>	<b>STEL</b>	
014808-60-7	10mg/m <sup>3</sup>	ND	0.1mg/m <sup>3</sup>	ND	
065997-16-2	%SiO <sub>2</sub> + 2 5mg/m <sup>3</sup>	ND	5mg/m <sup>3</sup>	ND	Respirable Dust
001314-13-2	5mg/m <sup>3</sup>	ND	5mg/m <sup>3</sup>	10mg/m <sup>3</sup>	Respirable Dust

**LEGEND:** (M) MAX. EXPOSURE LIMIT; (S) OCCUPATIONAL EXP. LIMIT; (R) SUPPLIERS REC. LIMIT, (+) PERCUTANEOUS RISK  
 VOC: COMPONENT = 0 grams/liter (CARB) AS APPLIED: 0 grams/liter (CARB)

**SECTION 3: PHYSICAL DATA**

**BOILING POINT:** 2230<sup>o</sup>C (4046<sup>o</sup>F) **SPECIFIC GRAVITY:** 2.45  
**VAPOR PRESSURE:** NONE **MELTING POINT:** ND  
**VAPOR DENSITY:** NA **EVAPORATION RATE:** NA  
 (AIR = 1) (BUTYL ACETATE = 1)  
**SOLUBILITY IN WATER:** VERY SLIGHT **pH (In Water):** 9 -10  
**COEFFICIENT of WATER/OIL DISTRIBUTION:** ND  
**APPEARANCE AND ODOR:** CHARCOAL COLORED, GRANULAR POWDER. NO DISTINCT ODOR.  
**ODOR THRESHOLD:** ND

**SECTION 4: FIRE AND EXPLOSION HAZARD**

**FLASH POINT:** NONE  
**CONDITIONS OF FLAMMABILITY:** NA  
**FLAMMABLE LIMITS:** **LEL:** NA **UEL:** NA  
**OSHA CLASS:** NA  
**AUTO IGNITION TEMP:** NONE  
**HAZARDOUS COMBUSTION PRODUCTS:** NONE  
**SENSITIVITY TO IMPACT:** NONE  
**SENSITIVITY TO STATIC DISCHARGE:** NA  
**EXTINGUISHNG MEDIA:** NA  
**SPECIAL FIRE FIGHTING PROCEDURES:** NOT IGNITABLE  
**UNUSUAL FIRE AND EXPLOSIVE HAZARDS:** NA

(NA= NOT APPLICABLE) (NE=NOT ESTABLISHED) (ND= NOT DETERMINED)

**SECTION 5 : HEALTH HAZARD DATA**

**PRIMARY ROUTES OF ENTRY:** INHALATION, SKIN CONTACT, EYE CONTACT

**HEALTH HAZARDS (ACUTE AND CHRONIC EXPOSURES)**

EYES: ACUTE – DUST MAY CAUSE IRRITATION OR INFLAMMATION. ABRASIVE TO EYES.  
 CHRONIC – REPEATED CONTACT MAY CAUSE CHEMICAL BURNS RESULTING IN CORNEAL DAMAGE.  
 SKIN CONTACT: ACUTE – IRRITATION/DISCOMFORT MAY OCCUR.  
 CHRONIC – (CAUSTIC) CHEMICAL BURNS CAN OCCUR.  
 SKIN ABSORPTION: ACUTE -- ND  
 CHRONIC -- ND  
 INHALATION: ACUTE – MILD & TEMPORARY DISCOMFORT TO RESPIRATORY TRACT.  
 CHRONIC – PERSISTENT COUGH. SHORTNESS OF BREATH.  
 INGESTION: ACUTE -- ND  
 CHRONIC -- ND

**CONDITIONS AGGRAVATED BY EXPOSURE:** PRE-EXISTING UPPER RESPIRATORY AND LUNG DISEASES (BRONCHITIS, ASTHMA, EMPHYSEMA).

**CARCINOGENIC DATA:** NTP: YES OSHA: NO IARC: YES (2A)  
 SILICA IS LISTED WITH IARC AS A CLASS 2A CARCINOGEN. CONTAINS CRYSTALLINE SILICA WHICH CAN CAUSE LUNG DAMAGE AND CANCER. RISK DEPENDS ON DURATION AND LEVEL OF EXPOSURE.  
 TERATOGENICITY: ND MUTAGENICITY: ND  
 EMBRYOTOXICITY: ND SYNERGISTIC MATERIAL: ND

**OVEREXPOSURE EFFECTS:** REPEATED, PROLONGED INHALATION OF EXCESSIVE QUANTITIES OF QUARTZ DUST MAY RESULT IN DELAYED LUNG DISEASE (SILICOSIS).

IRRITANCY: YES  
 SENSITIZER: YES

**EMERGENCY AND FIRST AID PROCEDURES:**

GENERAL: IN DRY FORM THE POWDER POSES LITTLE IMMEDIATE HAZARD. EXPOSURE OF SUFFICIENT DURATION TO WET MATERIAL CAN CAUSE TISSUE DAMAGE.

EYES: FLUSH WITH WATER FOR 15 MINUTES. AVOID RUBBING. GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

SKIN: WASH WITH MILD SOAP AND WATER. SEEK MEDICAL TREATMENT WITH LONG EXPOSURES TO WET PRODUCT.

INHALATION: REMOVE AFFECTED PERSON TO FRESH AIR. SEEK MEDICAL ATTENTION IF COUGHING OR OTHER SYMPTOMS DO NOT SUBSIDE.

INGESTION: GIVE 3 – 4 GLASSES OF WATER. **DO NOT INDUCE VOMITING.** GET MEDICAL ATTENTION.

**ACUTE TOXICITY EFFECTS:** NO DATA.

**SECTION 6: REACTIVITY DATA**

**STABILITY:** STABLE

**CONDITIONS TO AVOID:** NONE

**INCOMPATIBILITY (MATERIAL TO AVOID):** VERY STRONG OXIDIZING AGENTS MAY CAUSE FIRES. AVOID ACIDS AND AMMONIUM SALTS.

**HAZARDOUS DECOMPOSITION PRODUCTS:** SILICON TETRAFLUORIDE, A CORROSIVE GAS, WHEN CONTACTED BY HYDROFLUORIC ACID. WATER PRODUCES HYDRATION AND FORMATION OF CAUSTIC CALCIUM HYDROXIDE.

**HAZARDOUS POLYMERIZATION (REACTIVITY):** WILL NOT OCCUR.

**SECTION 7: SPILL OR LEAK PROCEDURES**

**STEPS TO BE TAKEN IN CASE OF MATERIAL IS RELEASED OR SPILLED:** USE DUSTLESS METHODS (VACUUM) AND PLACE IN CLOSABLE CONTAINERS FOR DISPOSAL. SCRAPE UP WET MATERIAL AND PLACE IN CONTAINERS. ALLOW TO DRY BEFORE DISPOSAL. WEAR PROTECTIVE EQUIPMENT AS SHOWN IN SECTION 8.

**WASTE DISPOSAL METHODS:** DISPOSE IN ACCORDANCE WITH LOCAL, STATE & FEDERAL REGULATIONS.

**ECOLOGICAL INFORMATION:**

**ECOTOXICITY:** NO RECOGNIZED UNUSUAL TOXICITY TO PLANTS OR ANIMALS.

**SECTION 8: SPECIAL PROTECTION INFORMATION**

**ENGINEERING CONTROLS:** LOCAL OR GENERAL EXHAUST AS NEEDED.

**RESPIRATORY PROTECTION:** AS REQUIRED. NIOSH-MSHA APPROVED RESPIRATORS (PAPER DISPOSABLE; ½ OR FULL FACE PIECE AIR PURIFYING; SUPPLIED AIR – DEPENDENT UPON PEL LEVELS).

<5X PEL --- ANY DUST RESPIRATOR.

5<10 PEL – ANY DUST RESPIRATOR (EXCEPT SINGLE USE OR ¼ MASK). ANY FUME OR HIGH EFFICIENCY PARTICULATE FILTER RESPIRATOR.

10<50 PEL – HIGH EFFICIENCY PARTICULATE FILTER RESPIRATOR WITH FULL FACEPIECE.

50<500 PEL – POWERED AIR-PURIFYING RESPIRATOR WITH PARTICULATE FILTER.

>500 PEL --- SELF-CONTAINED BREATHING APPARATUS.

**PROTECTIVE GLOVES:** NITRILE RUBBER. (DO NOT RELY ON BARRIER CREAMS.)

**EYE PROTECTION:** GOGGLES OR SAFETY GLASSES WITH SIDE SHIELDS.

**OTHER PROTECTIVE EQUIPMENT:** LONG SLEEVED SHIRTS AND PANTS. WHERE PROLONGED EXPOSURE TO UNHARDENED PRODUCT MAY OCCUR, WEAR IMPERVIOUS CLOTHING.

**SECTION 9: HANDLING & STORAGE**

**GENERAL:** STORE IN COOL, DRY SPACES. HANDLE IN MANNERS WHICH PREVENT DUST.

**SECTION 10: SUPPLEMENTAL INFORMATION**

**HMIS RATING**                      **HEALTH 2**                      **FLAMMABILITY 0**                      **REACTIVITY 0**

**DOT PROPER SHIPPING NAME:** DRY BUILDING MORTAR, NOT REGULATED.

**HAZARD CLASS:** NA

**UN NUMBER:** NA

**PACKING GROUP:** NA

**IMO SHIPPING DATA:** NOT REGULATED.

**ICAO/IATA SHIPPING DATA:** NOT REGULATED.

**TSCA (TOXIC SUBSTANCE CONTROL ACT):** ALL COMPONENTS ARE ON THE TSCA SUBSTANCE LIST.

**CERCLA (COMPREHENSIVE RESPONSE COMPENSATION and LIABILITY ACT):** ND

**SARA TITLE III**

SECTION 312 HAZARD CLASS: HAZARDOUS SUBSTANCE WITH DELAYED HEALTH EFFECTS.

SECTION 313 LISTED INGREDIENTS: CAS # 001314-13-2

**CALIFORNIA PROPOSITION 65:** The below list of compounds is known to the State of California to cause cancer, birth defects or other reproductive harm: CAS # 014808-60-7

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the accuracy of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects, which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations and orders.